

| DESCRIPTION 1 | | | | | | | | | | DESCRIPTION 2 | | |
|---------------|----------|----------|----------|----------|------------|---------------|-------------|----------|------------------------|---|---------------------------|------------|
| ANGLE | EQUAL | 3/4" | 3/4" | X | 1/8" | SS T304/T304L | MILL FINISH | APPROVED | [SRL 20'-0" TO 22'-0"] | ASTM A276, ASME SA276 | | |
| TYPE | KIND | SIZE 1 | SIZE 2 | | SIZE 3 | GRADE | FINISH | ORIGIN | LENGTH | STANDARDS & SPECIFICATIONS | | |
| LBA | E | E | E | X | 125 | N | | A | | SS T304/T304L SS T316/T316L DUPLEX 2205 | ASTM A276 | ASME SA276 |
| ANGLE-R | LBA | ANGLE | E | | 1/8" | SS T304/T304L | MILL FINISH | APPROVED | [SRL 20'-0" TO 22'-0"] | ASTM A928; ASTM A276 | ASME SA928; ASME SA276 | |
| ANGLE-R | A | UNEQUAL | U | | 125 | N | LASER FUSED | A | | | | |
| | | 1/2" D | 1/2" D | | 3/16" 188 | SS T316/T316L | LF | D | | | | |
| | | 3/4" E | 3/4" E | | 1/4" 250 | DUPLEX 2205 | | D | | | | |
| | | 1" F | 1" F | | 3/8" 375 | | | D | | | | |
| | | 1-1/4" G | 1-1/4" G | | 1/2" 500 | | | D | | | | |
| | | 1-1/2" H | 1-1/2" H | | 5/8" 625 | | | D | | | | |
| | | 2" I | 2" I | | | | | D | | | | |
| | | 2-1/2" J | 2-1/2" J | | | | | D | | | | |
| | | 3" K | 3" K | | | | | D | | | | |
| | | 3-1/2" L | 3-1/2" L | | | | | D | | | | |
| | | 4" M | 4" M | | | | | D | | | | |
| | | 5" N | 5" N | | | | | D | | | | |
| | | 6" O | 6" O | | | | | D | | | | |
| | | 8" P | 8" P | | | | | D | | | | |

FULL ANGLES ARE SOLD BY POUND / FULL THEORITICAL WEIGHT LENGHTS
LESS THAN FULL LENGHTS (ANGLE-R) SOLD BY EACH