



Class 150 # - CAST FITTINGS, ASTM A351 - Regular Pattern

COUPLINGS



Grade: ☐ T304/CF8 ☐ T316/CF8M
Connection: ☐ Threaded
Source: ☐ Import ☐ Domestic

DIMENSIONS

UOM: Inches/LBS

SELECT	SIZE	d1	BSPT., NPT		D1	BSP, D IN 2999	
			d3	L2		D3	L
☐	1/8	1/8	0.55	0.79	1/8	0.55	0.79
☐	1/4	1/4	0.73	1.06	1/4	0.73	0.98
☐	3/8	3/8	0.85	1.10	3/8	0.85	1.02
☐	1/2	1/2	1.04	1.42	1/2	1.04	1.34
☐	3/4	3/4	1.26	1.54	3/4	1.26	1.42
☐	1	1	1.56	1.69	1	1.56	1.69
☐	1 1/4	1 1/4	1.91	1.89	1 1/4	1.91	1.89
☐	1 1/2	1 1/2	2.15	1.89	1 1/2	2.15	1.89
☐	2	2	2.62	2.20	2	2.62	2.20
☐	2 1/2	2 1/2	3.31	2.56	2 1/2	3.31	2.56
☐	3	3	3.94	2.80	3	3.74	2.80
☐	4	4	5.08	3.27	4	4.80	3.27
☐	5	5	6.36	3.54	----	----	----
☐	6	6	7.28	3.96	----	----	----

Thread Pattern conform to ANSI / ASME B1.20.1, NPT
No Lead
Stainless Wrought Fittings conform To ASTM A182, Barstock to ASTM A479