



Project Name: _____
Job #: _____

Class 150# - CAST FITTINGS, ASTM A351 – MSS SP114 Heavy Pattern

HEAVY PATTERN 45° ELBOW



Grade: ☐ T304/CF8 ☐ T316/CF8M
Connection: ☐ Threaded ☐ Socket weld
Source: ☐ Import ☐ Domestic

DIMENSIONS

UOM: Inches/LBS

SELECT	SIZE	C	E	G	H	SB	SD
☐	1/8	0.69	0.20	0.09	0.75	0.43	0.39
☐	1/4	0.69	0.20	0.09	0.84	0.56	0.39
☐	3/8	0.81	0.21	0.10	1.01	0.69	0.39
☐	1/2	0.87	0.25	0.10	1.20	0.85	0.39
☐	3/4	1.00	0.27	0.12	1.46	1.07	0.51
☐	1	1.12	0.30	0.13	1.77	1.33	0.51
☐	1 1/4	1.31	0.34	0.14	2.15	1.68	0.51
☐	1 1/2	1.43	0.37	0.15	2.43	1.92	0.51
☐	2	1.68	0.42	0.17	2.96	2.41	0.63
☐	2 1/2	1.93	0.48	0.21	3.31	2.91	0.63
☐	3	2.18	0.55	0.23	4.00	3.54	0.63
☐	4	2.62	0.66	0.26	5.06	4.55	0.75

Thread Pattern conform to ANSI / ASME B1.20.1, NPT
Stainless Castings conform to ASTM A351
Stainless Wrought Fittings conform To ASTM A182, Barstock to ASTM A479
Manufactured in accordance to ISO 9001: 2000