


Project Name: _____
Job #: _____

150# CAST
A351
(45 Ell)

Class 150 # - CAST FITTINGS, ASTM A351 - Regular Pattern

45° ELBOW



Grade: ☐ T304/CF8 ☐ T316/CF8M
Connection: ☐ Threaded ☐ Socket weld
Source: ☐ Import ☐ Domestic

DIMENSIONS

UOM: Inches/LBS

SELECT	SIZE	d1	d2	d3	C	E	H	I
☐	1/8	1/8	0.63	0.53	0.24	0.63	0.24	0.08
☐	1/4	1/4	0.75	0.61	0.37	0.67	0.26	0.08
☐	3/8	3/8	0.89	0.77	0.38	0.75	0.24	0.08
☐	1/2	1/2	1.18	1.10	0.39	0.83	0.31	0.10
☐	3/4	3/4	1.42	1.34	0.43	0.94	0.39	0.10
☐	1	1	1.77	1.57	0.55	1.10	0.39	0.10
☐	1 1/4	1 1/4	2.22	1.91	0.61	1.30	0.43	0.10
☐	1 1/2	1 1/2	2.30	2.20	0.61	1.42	0.49	0.10
☐	2	2	2.83	2.68	0.65	1.65	0.51	0.10
☐	2 1/2	2 1/2	3.54	3.43	0.87	1.93	0.55	0.16
☐	3	3	4.17	4.00	0.98	2.13	0.59	0.16
☐	4	4	6.24	4.25	0.98	2.56	0.59	0.16

Thread Pattern conform to ANSI / ASME B1.20.1, NPT

No Lead

Stainless Wrought Fittings conform To ASTM A182, Barstock to ASTM A479