




Project Name: _____

Job #: _____

Class 150# - CAST FITTINGS, ASTM A351 - MSS **SP114 Heavy Pattern**

HEAVY PATTERN CAPS



Grade: ☐ T304/CF8 ☐ T316/CF8M
 Connection: ☐ Threaded ☐ Socket weld
 Source: ☐ Import ☐ Domestic

DIMENSIONS

UOM: Inches/LBS

SELECT	SIZE	C	E	G	G1	H	L	SB	SD
☐	1/8	0.25	0.20	0.09	0.09	0.75	0.68	0.43	0.39
☐	1/4	0.32	0.20	0.09	0.09	0.84	0.68	0.56	0.39
☐	3/8	0.36	0.21	0.10	0.10	1.01	0.81	0.69	0.39
☐	1/2	0.43	0.25	0.10	0.12	1.20	0.93	0.85	0.39
☐	3/4	0.50	0.27	0.12	0.13	1.46	1.06	1.07	0.51
☐	1	0.58	0.30	0.13	0.15	1.77	1.31	1.33	0.51
☐	1 1/4	0.67	0.34	0.14	0.17	2.15	1.62	1.68	0.51
☐	1 1/2	0.70	0.37	0.15	0.19	2.43	1.62	1.92	0.51
☐	2	0.75	0.42	0.17	0.22	2.96	1.75	2.41	0.63
☐	2 1/2	0.92	0.48	0.21	0.25	3.31	2.00	2.91	0.63
☐	3	0.98	0.55	0.23	0.29	4.00	2.25	3.54	0.63
☐	4	1.08	0.66	0.26	0.36	5.06	2.50	4.55	0.75

Thread Pattern conform to ANSI / ASME B1.20.1, NPT

Stainless Castings conform to ASTM A351

Stainless Wrought Fittings conform To ASTM A182, Barstock to ASTM A479

Manufactured in accordance to ISO 9001: 2000