


Project Name: _____
 Job #: _____

150# CAST
 A351
 (H Cplg)

Class 150 # - CAST FITTINGS, ASTM A351 -
Regular Pattern
HALF COUPLINGS



Grade: ☐ T304/CF8 ☐ T316/CF8M
 Connection: ☐ Threaded
 Source: ☐ Import ☐ Domestic

DIMENSIONS

UOM: Inches/LBS

SELECT	SIZE	d1	BSPT., NPT		D1	BSP, D IN 2999	
			d3	L2		D3	L
☐	1/8	1/8	0.56	0.43	1/8	0.55	0.43
☐	1/4	1/4	0.73	0.51	1/4	0.73	0.43
☐	3/8	3/8	0.85	0.55	3/8	0.85	0.47
☐	1/2	1/2	1.04	0.71	1/2	1.04	0.59
☐	3/4	3/4	1.26	0.79	3/4	1.26	0.67
☐	1	1	1.56	0.83	1	1.56	0.75
☐	1 1/4	1 1/4	1.91	0.94	1 1/4	1.91	0.87
☐	1 1/2	1 1/2	2.15	0.94	1 1/2	2.15	0.87
☐	2	2	2.62	1.10	2	2.62	1.02
☐	2 1/2	2 1/2	3.31	1.30	2 1/2	3.23	1.18
☐	3	3	3.94	1.42	3	3.74	1.30
☐	4	4	5.08	1.65	4	4.80	1.57

Thread Pattern conform to ANSI / ASME B1.20.1, NPT
 No Lead
 Stainless Wrought Fittings conform To ASTM A182, Barstock to ASTM A479